

HI-MORTAR RTB **(Roof Tile Bedding Mortar.)**

DESCRIPTION

Hi Mortar RTB is a special blend of cement, sand and high quality additives designed for all aspects of bedding ridges, barges and apexes on tiled roofs.

ADVANTAGES

Ready to use, consistent product, time and labour savings and to minimise waste
Suitable for all aspects of bedding ridges, barges and apexes
No sand or cement mess or waste on site
Performs well in warm and hot temperatures

PACKING

Hi Mortar RTB is available in 20kg bags.

STORAGE

Store in a dry Environment off concrete floors in the original unopened bag.

SAFETY

Hi Mortar RTB contains cement powders which can be harmful to the skin. During use, avoid inhalation of dust and contact with the skin and eyes. Wear suitable clothing, gloves, eye protection and respiratory protective equipment.

COVERAGE

Each bag of Hi Mortar RTB will yield approximately 12 litres of fresh mortar when mixed with approximately 2.0 litres of clean water.

MIXING

To overcome any potential segregation that has occurred during transit, thoroughly mix the maxi bag contents before use.

Place the required amount of Roof Tile Bedding Mortar into a mixer or onto a non-absorbent surface and slowly add 3- 4 litres of clean water per 20kg bag, ensuring it does not wash away any of the cement. Mix the mortar thoroughly to ensure a consistent mix.

Refrain from excessive water addition as this will weaken the mix, delay setting times and adversely affect durability.

Form a mortar bed of approximately 50mm in width on both sides and ends of the ridge or hip tile. Bed the tile in position and remove any mortar that may have been squeezed out when placing the tile.

Use a trowel and sponge to neaten the bedding mortar to provide a clean face for the pointing mix to be applied later.



This Product is Formulated and Labelled and Commercial use only
For Best Results and Safest Usage, User is Specialty Directed to Consult.

Product Warranty: All recommendations, statements and technical data contained herein are based on tests we believe to be reliable and correct, HI BOND warrants its products to be free of mfg. Defects and that, at the time and place of shipment, our material will meet current published physical properties when applied within HI BOND'S directions and tested in HI BOND'S standards. HI BOND'S facility is limited to replacement of material found to be defective. As HI BOND has no control over the use to which others may put its products. It is recommended that the product be tested to determine if suitable for a specific application and / or our information is valid in particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, applications and proper installation of each product. Nothing contained herein shall be construed to be a recommendation to use or as a license to operate under or to infringe any existing patents.