

HI-RAIN GUARD

(Waterproof Damp free decorative wall coating.)

DESCRIPTION

HI-RAIN GUARD is a ready to use water based single component waterproof coating. It provides excellent resistance to fungus and algae. It is an elastomeric coating that fills & covers hairline cracks and maintains a clean surface.

USE

Exterior surfaces of Masonry walls, Concrete, RCC, Pre-cast, Concrete panels, rain lashed walls, chajjas & parapet walls.

ADVANTAGES

- Easy To Apply by Brush, Roller or Spray.
- Mold and Mildew resistance
- Long durability
- Covers hair line cracks Decorative
- Non toxic, Eco-friendly

Priming: Where necessary to seal of dust and cohesiveness to improve the substrate, Apply HI-PRIME as a Primer.

TECHNICAL DATA

Color	: White and Dark basis
Form	: R.F.U
Specific Gravity	: 1.3
Bonding	: Excellent
Appln Temp	: >5° C
Service Temp	: 20°C - 55°C
Solid Content	: >65%
Accelerated Weathering	: UV Resistant

APPLICATION

Surface Preparation: Clean the surface thoroughly with out any loose material, oil, grease etc by wire brushing/ shot blasting and finally clean surface with Vacuum. All surface cracks up to 3 mm width should be filled up with Hi-Seal crack seal paste. Cracks more than 3 mm and all separation gaps should be filled up with Hi-Fix modified mortar modified mortar.

Application: Apply Two coats of HI-Rain Guard on the properly primed surface, by using a Roller or Brush. Each coat apply with an interval of 2-3 hrs.

This Product is Formulated and Labelled and Commercial use only

For Best Results and Safest Usage, User is Specialty Directed to Consult.

Product Warranty: All recommendations, statements and technical data contained herein are based on tests we believe to be reliable and correct, HI BOND warrants its products to be free of mfg. Defects and that, at the time and place of shipment, our material will meet current published physical properties when applied within HI BOND'S directions and tested in HI BOND'S standards. HI BOND'S facility is limited to replacement of material found to be defective. As HI BOND has no control over the use to which others may put its products. It is recommended that the product be tested to determine if suitable for a specific application and / or our information is valid in particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, applications and proper installation of each product. Nothing contained herein shall be construed to be a recommendation to use or as a license to operate under or to infringe any existing patents.